

2017-01 r4

2017-01 r4

© 2017 MTB [CZ] & TT-West [US]

© 2017 MTB [CZ] & TT-West [US]

2.42 in >7mm un-plug clearance _ (62mm) **Mounting Template** + wire access as needed 1.79 in (45.5mm) Thickness: 0.28 in 1.24 in (7mm) 0.756 in (31mm) -1 46 in (19.2mm) (37mm) 0.2 in below centers mounting – M2 a surface AUX1 ~0.5 in 0 0 0.86 in (12.6mm) Longitudinal 0 0 **-** М2 b Adjustment M2.5 or #3 poz1 **O O** panhead 0 0 COM Nominal 0.25 in 2 places Lateral 0 0 Offset to Adjustment 0.89 in Throw-bar (mtb)1.69 in (22.5mm) 1:1 Full Size ~0.5 in (12.6mm Print Ref: 2 inch | 50.8 mm nominal 12-position Plug (M) c/l to rod c/l 2 x 6 - 3.5mm pitch <u>1.69</u> in (ba<u>se</u>, 0.5 +/- 0.1 in 12-position Socket (F) (43mm) Wire Push-in: 16-26 AWG 2 x 6 - 3.5mm pitch 1.46 in (37mm) actuator adjustment centers screwdriver access as needed Available From: **MRCS** Railroad **MTB MP5 Advanced Switch Motor** Control Systems **Mounting & Dimensions** www.modelrailroadcontrolsystems.com

1:1 Full Size